

EM

Piede Snodato in Acciaio Zincato

Zinc Plated Articulated Foot

COD.	A	M	B	H	Carico Max Statico Maximum Load daN	U.V.
A4EM40/8	40	08MA	56	25	400	4
A4EM40/10	40	10MA	70	25	400	4
A4EM40/12	40	12MA	70	25	400	4
A4EM60/12	60	12MA	70	23	600	4
A4EM60/16	60	16MA	70	23	600	4
A4EM80/16	80	16MA	128	23	1000	4
A4EM80/20	80	20MA	128	25	1000	4
A4EM100/16	100	16MA	165	25	1200	4
A4EM100/20	100	20MA	165	25	1200	4

Caratteristiche

Caratteristiche Specifiche:

Livellamento laterale di 15° circa

Materiale Base: Acciaio cromato

Corredo Base: Suola antiscivolo in dotazione

Materiale Stelo: Acciaio zincato

Tipo Stelo: Snodato (testa sferica)

Presentazione Prodotto:

Stelo fornito già assemblato alla base

Product specification

Specific Features:

Lateral adjustment approx 15°

Base Material: Chromium plated Steel

Base Outfit: Non-slip pad enclosed

Spindle Material: Zinc plated steel

Spindle Type: Swivel (spheric head)

Product Presentation:

Spindle supplied already assembled to the base

