

# NS

## Base in Nylon con Snodo, Inserto Filettato e Suola Antiscivolo

### Machine Leveling Foot with Female Adjustable Thread and non-Slip Rubber Insert

COD.	A	H	H1	C	B	SW	M	Carico max Max Load daN	U.V.
A3NS3006	30	18	7	24	8,5	14	06MA	600	24
A3NS4006	40	18	7	24	8,5	14	06MA	900	24
A3NS4008	40	18	7	24	8,5	14	08MA	900	24
A3NS4010	40	18	7	24	8,5	14	10MA	900	24
A3NS6008	60	18	7	24	8,5	14	08MA	1200	24
A3NS6010	60	18	7	24	8,5	14	10MA	1200	24
A3NS8008	80	18	7	24	8,5	14	08MA	1400	24
A3NS8010	80	18	7	24	8,5	14	10MA	1400	24
A3NS8012	80	21	7	25	15	17	12MA	1400	24

#### Caratteristiche

##### Materiale Base:

Nylon caricato vetro con inserto

##### Tipo Base:

Non fissabile al suolo

##### Materiale Inserto:

Acciaio zincato

##### Tipo Inserto:

Femmina snodato ES14 – ES17

per art. A3NS8012

##### Corredo Stelo:

Suola antiscivolo in dotazione

##### Nota:

Accoppiabile con qualsiasi stelo filettato

#### Product specification

##### Base Material:

Fiberglass reinforced Nylon

##### Base Type:

Not fixable to the ground

##### Thread Material:

Zinc plated steel

##### Thread Type:

Female adjustable EX14 – EX17

for art. A3N8012

##### Base Outfit:

Equipped with non-slip rubber sole

##### Note:

Can be matched to any threaded stud

