

# XS75

## Piede Snodato con Base e Stelo in Acciaio Inox AISI 304

### Articulated Foot with AISI 304 Stainless Steel Base and Stud

**INOX**  
Stainless Steel

| Cod.         | A  | M    | B   | C   | H  | Chiave Spanner | Carico Max Max Load daN | U.V. |
|--------------|----|------|-----|-----|----|----------------|-------------------------|------|
| A5XS75/16060 | 75 | 16MA | 60  | 103 | 26 | 13             | 1900                    | 8    |
| A5XS75/16090 | 75 | 16MA | 90  | 133 | 26 | 13             | 1900                    | 8    |
| A5XS75/16105 | 75 | 16MA | 105 | 148 | 26 | 13             | 1900                    | 8    |
| A5XS75/16125 | 75 | 16MA | 125 | 168 | 26 | 13             | 1900                    | 8    |
| A5XS75/16155 | 75 | 16MA | 155 | 198 | 26 | 13             | 1900                    | 8    |
| A5XS75/16165 | 75 | 16MA | 165 | 208 | 26 | 13             | 1900                    | 8    |
| A5XS75/16205 | 75 | 16MA | 205 | 248 | 26 | 13             | 1900                    | 8    |
| A5XS75/20086 | 75 | 20MA | 86  | 132 | 26 | 17             | 2100                    | 8    |
| A5XS75/20116 | 75 | 20MA | 116 | 162 | 26 | 17             | 2100                    | 8    |
| A5XS75/20141 | 75 | 20MA | 141 | 187 | 26 | 17             | 2100                    | 8    |
| A5XS75/20206 | 75 | 20MA | 206 | 252 | 26 | 17             | 2100                    | 8    |
| A5XS75/24096 | 75 | 24MA | 96  | 142 | 26 | 19             | 2300                    | 8    |
| A5XS75/24122 | 75 | 24MA | 122 | 168 | 26 | 19             | 2300                    | 8    |
| A5XS75/24152 | 75 | 24MA | 152 | 198 | 26 | 19             | 2300                    | 8    |
| A5XS75/24182 | 75 | 24MA | 182 | 228 | 26 | 19             | 2300                    | 8    |
| A5XS75/24300 | 75 | 24MA | 300 | 346 | 26 | 19             | 2300                    | 8    |

#### Caratteristiche

##### Materiale Base:

Anima interna in poliammide + FV;  
rivestimento esterno in acciaio inox AISI 304;  
antivibrante in gomma termoplastica SEBS 55 shore colore nero.

**Materiale Stelo:** Acciaio inox AISI 304

**Tipo Stelo:** Snodato

##### Presentazione Prodotto:

Stelo fornito assemblato alla base

##### Note:

L'antivibrante costampato consente una perfetta aderenza con la base in acciaio. La conseguente assenza di cavità interne rende il piede estremamente sanificabile.

#### Product specification

##### Base Material:

Internal part made of reinforced polyamide;  
external covering made of stainless steel AISI 304;  
anti-slip pad made of SEBS Rubber 55 shore black colour.

**Spindle Material:** Stainless steel AISI 304

**Spindle Type:** Articulated

##### Product Presentation:

Spindle supplied assembled to the base

##### Note:

The comoulded anti-slip rubber pad adheres perfectly to the steel base thus the absence of internal cavities makes the foot extremely easy to clean and sanitize.



Ø75

