

XS95

Piede Snodato con Base e Stelo in Acciaio Inox AISI 304

Articulated Foot with AISI 304 Stainless Steel Base and Stud

INOX
Stainless Steel

| Cod. | A | M | B | C | H | Chiave Spanner | Carico Max Max Load daN | U.V. |
|--------------|----|------|-----|-----|----|----------------|-------------------------|------|
| A5XS95/16060 | 95 | 16MA | 60 | 103 | 26 | 13 | 2200 | 8 |
| A5XS95/16090 | 95 | 16MA | 90 | 133 | 26 | 13 | 2200 | 8 |
| A5XS95/16105 | 95 | 16MA | 105 | 148 | 26 | 13 | 2200 | 8 |
| A5XS95/16125 | 95 | 16MA | 125 | 168 | 26 | 13 | 2200 | 8 |
| A5XS95/16155 | 95 | 16MA | 155 | 198 | 26 | 13 | 2200 | 8 |
| A5XS95/16165 | 95 | 16MA | 165 | 208 | 26 | 13 | 2200 | 8 |
| A5XS95/16205 | 95 | 16MA | 205 | 248 | 26 | 13 | 2200 | 8 |
| A5XS95/20086 | 95 | 20MA | 86 | 132 | 26 | 17 | 2400 | 8 |
| A5XS95/20116 | 95 | 20MA | 116 | 162 | 26 | 17 | 2400 | 8 |
| A5XS95/20141 | 95 | 20MA | 141 | 187 | 26 | 17 | 2400 | 8 |
| A5XS95/20206 | 95 | 20MA | 206 | 252 | 26 | 17 | 2400 | 8 |
| A5XS95/24096 | 95 | 24MA | 96 | 142 | 26 | 19 | 2600 | 8 |
| A5XS95/24122 | 95 | 24MA | 122 | 168 | 26 | 19 | 2600 | 8 |
| A5XS95/24152 | 95 | 24MA | 152 | 198 | 26 | 19 | 2600 | 8 |
| A5XS95/24182 | 95 | 24MA | 182 | 228 | 26 | 19 | 2600 | 8 |
| A5XS95/24300 | 95 | 24MA | 300 | 346 | 26 | 19 | 2600 | 8 |

Caratteristiche

Materiale Base:

Anima interna in poliammide + FV;
rivestimento esterno in acciaio inox AISI 304; antivibrante in gomma termoplastica SEBS 55 shore colore nero.

Materiale Stelo: Acciaio inox AISI 304

Tipo Stelo: Snodato

Presentazione Prodotto:

Stelo fornito assemblato alla base

Note:

L'antivibrante costampato consente una perfetta aderenza con la base in acciaio. La conseguente assenza di cavità interne rende il piede estremamente sanificabile.

Product specification

Base Material:

Internal part made of reinforced polyamide; external covering made of stainless steel AISI 304; anti-slip pad made of SEBS Rubber 55 shore black colour.

Spindle Material: Stainless steel AISI 304

Spindle Type: Articulated

Product Presentation:

Spindle supplied assembled to the base

Note:

The comoulded anti-slip rubber pad adheres perfectly to the steel base thus the absence of internal cavities makes the foot extremely easy to clean and sanitize.



Ø95

